Heat

- If two bodies are in contact but initially have different temperatures, heat will transfer or flow between them if they are brought into contact.
- heat is the energy transferred, given the symbol Q.

Temperature and Equilibrium

Temperature is Energy per Degree of Freedom

Heat flows form hotter to colder object

Until temperatures are equal

Faster if better thermal contact

Even flows at negligible Δt (for reversible process)

The Unit of Temperature is the Kelvin

Absolute zero (no energy) is at 0.0 K

Ice melts at 273.15 Kelvin (0.0 C)

Fahrenheit scale is arbitrary

State Variables of System

State Variables - Definition

Measurable Static Properties

Fully Characterize System (if constituents known)

e.g. Determine Internal Energy, compressibility

Related by Equation of State


State Variables: Measurable Static Properties

- Temperature measure with thermometer
- Volume (size of container or of liquid in it)
- Pressure (use pressure gauge)
- Quantity: Mass or Moles or Number of Molecules
 - Of each constituent or phase (e.g. water and ice)

Heat and Work are Processes

- Processes accompany/cause state changes
 - Work along particular path to state B from A
 - Heat added along path to B from A
- Processes are not state variables
 - Processes change the state!
 - But Eq. Of State generally obeyed


Thermodynamic Systems



The state variables are changed only in response to Q and W

No other work or heat enters

Work



Find Work if piston moves Δx :

$$W = F \Delta x = pA \Delta x = p\Delta V$$

In General:
$$W_{fi} = \int_{i}^{f} p(V,T) dV$$

Variables in First Law

- Q is the Heat Added
 - Could find from Temperature Gradient
 - But need Heat Conductivity and Area
 - Generally determine from First Law
- W is the Work done by system
 - Equal to pDV
- U is the Internal Energy of system
 - It is determined by state variables
 - From equipartition, proportional to T

Internal Energy

Based on Equipartition:

-each coordinate of each particle

$$1/2 \text{ m} < v_x^2 > = 1/2 \text{ m} < v_y^2 > = 1/2 \text{ k}_B T$$

 $1/2 \mu < v_{rel}^2 > = 1/2 \text{ k}_B T$...molecule

For an ideal monatomic gas: U(T)=3/2 N k T

For an ideal diatomic molecular gas: U(T)=5/2 N k T (no vibration)


Thermodynamic cycles

A thermodynamic cycle is any process that brings a system back to its original state.

The cycle involves a path in state space over which various processes may act.

Addition/Removal of heat and work are typical processes.

Often the objective is to get work from heat or vice versa, as in a heat engine or heat pump.





HEAT in at T₂

HEAT ENGINE WORK as

Mechanical E

HEAT
Out at T₁

Energy Conserved $Q(\text{in at } T_2) = W_{cycle} + Q(\text{out at } T_1)$

Heat Engine Efficiency: ε


$$\varepsilon = \frac{W_{cycle}}{Q(\text{in at } T_2)}$$

Reversibility of Cycle

We showed that any leg of this cycle is reversible.

Therefore, the entire cycle (heat engine) could operate in reverse


In this case the total Work and the Heat flow will be reversed.



Operated in reverse it is a refrigerator that removes heat at the lower temperature

Or a heat pump delivering heat at the temperature T₂

Why Carnot is Maximum Say a heat engine exceeded Carnot Limit



Hook it to a perfect gas heat pump with the same T₁

Net Effect: Heat Q_{env} becomes work W_{net}

Second law of Thermodynamics

No process shall have the only result that Heat is turned into Work

or

No process shall have the only result that Heat is transferred from cooler to hotter.

The second law is the formal statement of the irreversibility of Nature on a classical scale: friction can irreversibly convert mechanical energy into heat; nothing can reverse this process.